



三片式陶瓷球阀
3-PC Ceramic Ball Valve

技术规范 Technical Specification

设计与制造 Design and Manufacture		API 6D / GB/T12237
连接端尺寸 Connection End	结构长度 Face-to-face Dimension	ASME B16.10 / GB/T12221
	法兰尺寸 Flange End	ASME B16.5 / GB/T9113
检验与试验 Inspection & Test		API598 / GB/T13927
材料 Material	碳钢 Carbon steel	GB/T12229
	不锈钢 Stainless steel	GB/T12230
标志Mark		GB/T12220
供货Delivery		GB/T12252

主要部件材料 Material Specification

序号No.	名称Name	材料Material	序号No.	名称Name	材料Material
1	中阀体 Middle body	WCB/CF8	8	垫圈 Washer	柔性石墨 Flexible graphite
2	左右阀体 Body	WCB/CF8	9	填料 Packing	PTFE
3	阀座 Seat	高强度结构陶瓷 High strength structural ceramic	10	填料压盖 Gland	WCB/CF8
4	球体 Ball	高强度结构陶瓷 High strength structural ceramic	11	阀杆 Stem	SS316/SS316L
5	O型圈 O-ring	氟橡胶Viton	12	锁紧螺母 Nut	A194-2H/B8
6	双头螺柱 Stud	A193-B7/B8	13	手柄 Lever	SS316/SS316L
7	螺母 Nut	A194-2H/B8			

GB/T 9113 ASME B16.5

DN	NPS	L	L1	D
15	1/2"	72	10	22
20	3/4"	85	13	28
25	1"	90	13	35
32	1 1/4"	112	16	43
40	1 1/2"	120	16	49
50	2"	145	18	62
65	2 1/2"	185	18	77
80	3"	215	20	90
100	4"	270	20	115

注：更多尺寸，请联系有氟密工程师。

Note: For more size, please consult our engineer.